

Release Note - advanced notification October 2022

Generic (Field) Values handling

As already informed earlier this year, we are going to change the section handling for custom fields (generic values).

So far, custom field data was available (where filled) in the section 'GENERIC_VALUES' as a map of key-value pairs with the key being the field name (applicable to company and traveller profiles).

The screenshot displays a REST client interface. At the top, a GET request is shown with the URL: `https://hurricane.umbrellanet.ch/uf-test/api/v1/profiles/company/2976152b-0a58-4c8b-ae1e-22393e910da6?sections=GENERIC_VALUES`. Below the URL bar, tabs for 'Params', 'Authorization', 'Headers (8)', 'Body', 'Pre-request Script', 'Tests', and 'Settings' are visible. The 'Params' tab is active, showing a table of query parameters.

	KEY	VALUE
☒	sections	GENERIC_VALUES
☐	sections	PUBLISH_STATES
☐	sections	MEMBERSHIPS
☐	sections	CREDIT_CARDS
	Key	Value

Below the table, the 'Body' tab is active, showing the JSON response in 'Pretty' format:

```
1 {
2   "uuid": "2976152b-0a58-4c8b-ae1e-22393e910da6",
3   "externalNr": "101010011",
4   "name": "API Testing",
5   "shortname": "APIT",
6   "data": {
7     "genericValues": {
8       "Oldcustomfield": "goodbye"
9     }
10  }
11 }
```

Starting from November 1st, 2022 we will only support the new section `GENERIC_FIELD_VALUES` for getting custom field data (where filled).

GET
https://hurricane.umbrellanet.ch/uf-test/api/v1/profiles/company/2976152b-0a58-4c8b-ae1e-22393e910da6?sections=GENERIC_FIELD_VALUES

Params
Authorization
Headers (8)
Body
Pre-request Script
Tests
Settings

Query Params

	KEY	VALUE
☒	sections	GENERIC_FIELD_VALUES
☐	sections	PUBLISH_STATES
☐	sections	MEMBERSHIPS
☐	sections	CREDIT_CARDS
	Key	Value

Body
Cookies
Headers (18)
Test Results

Pretty
Raw
Preview
Visualize
JSON

```

1  {
2    "uuid": "2976152b-0a58-4c8b-ae1e-22393e910da6",
3    "externalNr": "101010011",
4    "name": "API Testing",
5    "shortname": "APIT",
6    "data": {
7      "genericFieldValues": [
8        {
9          "field": {
10             "uuid": "ad5e6a7e-82c6-4f10-8e9a-6d6de4ea003f",
11             "name": "Oldcustomfield"
12           },
13          "value": "goodbye"
14        }
15      ]
16    }
17  }

```

This new section includes besides of the field name and the value also the UUID number of the custom field. Updates to a custom field can be done using the field name or uuid, where uuid however has priority over the field name if it is provided.

We are going to remove the old 'GENERIC_VALUES' section on October 31st, 2022.

For the time being, either of the options (GENERIC_VALUES or GENERIC_FIELD_VALUES) can be used. However, we kindly ask you to perform the necessary changes until end of October latest or get in touch ASAP if that is not possible.